

Multimedia-Programmierung

Übung 7


Ludwig-Maximilians-Universität München
Sommersemester 2012

Today

- Sprite animations in 
- Advanced collision detection
- Sound

Keyframe Animations


- Keyframes are defined
- Intermediate steps are interpolated
- Basic interpolators/tweens/... built into many programming environments (e.g. Flash, JavaFX)
- Examples: motion, color, shape



Keyframe Animations

Keyframe Animations in Pygame

- Pygame has no built-in interpolators
- Logic has to be added by the programmer
- Question: How can we calculate the intermediate points?



Horizontal Animation (old slides)



```
import pygame
from pygame.locals import *
from sys import exit

player_image = 'head.jpg'
pygame.init()

screen = pygame.display.set_mode((640, 280), 0, 32)
pygame.display.set_caption("Animate X!")
mouse_cursor = pygame.image.load(player_image).convert_alpha()

x = 0 - mouse_cursor.get_width()
y = 10

while True:
    for event in pygame.event.get():
        if event.type == QUIT:
            exit()
    screen.fill((255,255,255))
    if x > screen.get_width():
        x = 0 - mouse_cursor.get_width()
    screen.blit(mouse_cursor, (x, y))
    x+=10
    pygame.display.update()
```

Result:



Sprite Animations

- Animations consist of frames that are displayed one after another



Frame 1

...

Frame 7



- Either imported as single graphics or with sprite sheets

Graphic from <http://shinylittlething.com/2009/07/21/pygame-and-animated-sprites/>

Contains small tutorial on creating animations with sprite sheets in Pygame


Sprite Sheets & Spriting

- Sprite sheets contain all possible movements for a character
 - Each Sprite should have the same size for easy slicing in software
 - Spriting means to adapt existing sprites or sprite sheets or create new ones (e.g. with empty outlines)



Creating Sprite Sheets

- Sprite Sheets in WWW usually do not have equal sizes for each sprite
- Editing needed, e.g. with Photoshop, Gimp, Pixin etc.
- Pay attention to positioning of character and background color (should not appear in character)



Pixin (Mac only)

Slicing Sprite Sheets



```
def load_sliced_sprites(self, w, h, filename):
    images = []
    master_image = pygame.image.load(os.path.join('ressources',
                                                filename)).convert_alpha()

        master_image.set_colorkey((255,0,255))
    master_width, master_height = master_image.get_size()

    for i in xrange(int(master_width/w)):
        images.append(master_image.subsurface((i*w,0,w,h)))

    return images
```

set transparent color,
background color of
sprite sheet

create subsurfaces

More specialized slicing function may be needed due to incompatible sprite sheet (e.g. with borders)

First Sprite Animation 1

```

import os, pygame
from pygame.locals import *

def load_sliced_sprites(self, w, h, filename):
    ...

class BombWithAnimation(pygame.sprite.Sprite):
    def __init__(self, color, initial_position, fps):           remember the current frame
        pygame.sprite.Sprite.__init__(self)
        self.act_frame = 0                                         ← create the frames (defined later)
        # create the images for the animation
        self.frames = load_sliced_sprites(20,20, „exploded-sprite.png“)
        self.image = self.frames[0]
        self.rect = self.image.get_rect()
        self.rect.topleft = initial_position
        self.fps = fps
        self.change_time = 1.0/self.fps
        self.time = 0

    def update(self, time_passed):
        self.time += time_passed
        if self.time >= self.change_time:
            self.act_frame = (self.act_frame + 1) % len(self.frames) ← Frame changed?
            self.image = self.frames[self.act_frame]                      ← change frame
            self.time = 0

```

First Sprite Animation 2



```
...
pygame.init()

screen = pygame.display.set_mode((640, 480), 0, 32)
bomb1 = BombWithAnimation((0,0),4)
clock = pygame.time.Clock()

while True:
    for event in pygame.event.get():
        if event.type == QUIT:
            exit()
    screen.fill((100, 200, 0))
    time_passed = clock.tick() / 1000.0
    bomb1.update(time_passed)
    screen.blit(bomb1.image,bomb1.rect)
    pygame.display.update()
```

Multiple Parallel Animations

```
...
pygame.init()

screen = pygame.display.set_mode((640, 480), 0, 32)
bomb1 = BombWithAnimation((0,0),4)
bomb2 = BombWithAnimation((40,40),2)
clock = pygame.time.Clock()


while True:
    for event in pygame.event.get():
        if event.type == QUIT:
            exit()
    screen.fill((100, 200, 0))
    time_passed = clock.tick() / 1000.0
    bomb1.update(time_passed)
    screen.blit(bomb1.image,bomb1.rect)
    bomb2.update(time_passed)
    screen.blit(bomb2.image,bomb2.rect)
    pygame.display.update()
```

two bombs in two
different framerates

Collision Detection

Rect

- Rect provides several methods to test collisions
<http://www.pygame.org/docs/ref/rect.html>
- `Rect.collidepoint(point)` tests whether a point is within the Rect's area




True




False
X

- `Rect.colliderect(rect)` tests whether two Rects intersect



True



False

Collision Detection

Rect II

- `Rect.collidelist(list)` tests whether the Rect collides with **at least one** Rect in the given list
- `Rect.collidelistall(list)` tests whether the Rect collides with **all** Rects in the list
- `Rect.collidedict(dict)` tests whether the Rect collides with **at least one** Rect in the given dictionary
- `Rect.collidedictall(dict)` tests whether the Rect collides with **all** Rects in the dictionary

Collision Detection

Sprites

- The module `sprite` provides several methods to test collision
<http://www.pygame.org/docs/ref/sprite.html>
- `sprite.spritecollide(...)` returns a list of sprites within a group that intersect with a given sprite
- `sprite.collide_rect(a,b)` checks whether two sprites intersect (must have rects)
- `sprite.collide_circle(a,b)` checks whether the radius of two sprites intersect. Radius attribute should be defined in the sprite.



False



True

Collision Detection

Sprites 2

- `sprite.groupcollide(a,b)` returns a list of sprites of two groups that intersect
- `sprite.collide_mask(a,b)` checks whether two Sprites collide on a bitmap level (non-transparent pixels overlap)

```
if pygame.sprite.collide_mask(head1,head2):
    print "collide"
```



False



True

Collision Detection

Masks

- Masks are 1bit per pixel representations of areas that can collide
- Module mask contains functions and classes to create and use masks

<http://www.pygame.org/docs/ref/mask.html>

- `mask.from_surface(surface,threshold=127)` creates a mask of a surface. Threshold defines the alpha value that counts as collideable
- Class Mask contains methods to work with classes

Original



Mask



collision area

Collision Detection

Conclusion


- Pygame offers various ways to check for collisions
- **Choose your collision detection algorithm wisely depending on the task**
- Pixel based collision detection is precise but slow
- Rect or radius based collision detection is fast but imprecise



Sound


- Sound is an essential part of multimedia applications
- Provides immediate feedback about an action
- Supports realism (e.g. games)
- Provides accessibility (e.g. for blind people)
- ...

Sound



vs.

No Sound





Sound in Pygame

Mixer

- Sounds are controlled using the `pygame.mixer` interface
- Mixer must be initialized
`pygame.mixer.init(frequency,size,channels,buffer)`
- Automatically initialized with `pygame.init()` using the default values
- Default values can be changed using
`pygame.mixer.pre_init()`
- The mixer “mixes” the sounds in background threads
 - Sounds are not blocking the rest of the application logic

Sound in Pygame

Sound Object

- `pygame.mixer.Sound` provides a class to load and control sound files (OGG and uncompressed WAV)
- `Sound.play(loops=0, maxtime=0, fade_ms=0)` plays the sound file
- Other methods: `stop()`, `fadeout(time)`, `set_volume(value)` etc.

playing a sound file

```
click_sound = pygame.mixer.Sound("click.wav")
click_sound.play()
```

playing a sound file in a loop 4(!) times

```
click_sound = pygame.mixer.Sound("click.wav")
click_sound.play(3)
```

Sound in Pygame

Channels

- A channel represents one of the channels that are mixed by the soundcard
- `Sound.play()` returns a Channel object (or None if all channels are blocked)
- Provides methods to manipulate the sound and create useful effects (e.g. `Channel.set_volume(left, right)`)

playing a sound file from the right speaker only

```
channel = click_sound.play()  
channel.set_volume(0.0,1.0)
```

Sound in Pygame

Stereo Panning

- Create the illusion that sound is coming from a specific point at the screen
- Manipulate the volume of the different speakers
- Can be used to make a sound “move” over the screen

stereo panning function

```
def stereo_pan(x_coord, screen_width):
    right_volume = float(x_coord) / screen_width
    left_volume = 1.0 - right_volume
    return (left_volume, right_volume)
```

From: W. McGugan, Beginning Game Development with Python and Pygame, Apress 2007

Music in Pygame


- Don't use pygame.mixer but `pygame.mixer.music`
- It enables **streaming** music which means that the file will be read in small chunks
- Supports MP3 and OGG files (OGG better supported across platforms)
- Other Methods include `stop()`, `pause()`, `rewind()` etc.
- **Attention:** only one song can be streamed at the same time

playing a song using pygame

```
pygame.mixer.music.load("music.ogg")
pygame.mixer.music.play()
```

Creating your own Sound

- Record real sounds and edit them
- Free sound editor Audacity (
<http://audacity.sourceforge.net/?lang=de>)



Useful Links

- Pygame Sprite Tutorial
<http://kai.vm.bytemark.co.uk/~piman/writing/sprite-tutorial.shtml>
- Pygame API !!!!
<http://www.pygame.org/ctypes/pygame-api/>